



**T70 1**

**The classic for lifting applications**

## Characteristics

- High-sensitivity two-step push button.
- Multiband Radio with Full-Duplex communication
- Highly customizable
- LCD display
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Frequency management against interferences

## Specifications

Transmitter	T70 1
Stop Function	Cat. 3 - PLd
Ingress Protection	IP65/NEMA4
Anti condensation system	na
Frequency Band	Multiband (400 - 930 MHz)
Main Mechanisms (Max. #)	Pushbutton (6)
Auxiliary Mechanisms	Toggle & Rotary switches
Removable EEPROM	External
Battery Model	BT06K
Battery Life	10h
Operating Temperature Range	-20C +70C (-4F +158F)
Weight (with Battery) Grams	460
Harness	Hand Strap / Shoulder Strap
Display	2x12 Char LCD
Cable Connection	na
Range Limiter	YES
Associated Receivers	R06/R13/R70/RCAN/MP08

## Associated Applications



### HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN  
 Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · [tlc@ikusitlc.com](mailto:tlc@ikusitlc.com) · [www.ikusitlc.com](http://www.ikusitlc.com)

### IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES

